MARTIN MARIETTA ENERGY SYSTEMS LIBRARIES

3 4456 0070881 1

ORNL/TM-9976

ornl

OAK RIDGE NATIONAL LABORATORY

MARTIN MARIETTA

A Waste Package Performance Assessment Code with Automated Sensitivity-Calculation Capability

B. A. Worley
J. E. Horwedel

OAK RIDGE NATIONAL LABORATORY
CENTRAL RESEARCH LIBRARY
CIRCULATION SECTION
4500N ROOM 175
LIBRARY LOAN COPY
DO NOT TRANSFER TO ANOTHER PERSON
If you wish someone else to see this report, send in name with report and the library will arrange a loan.

OPERATED BY
MARTIN MARIETTA ENERGY SYSTEMS, INC.
FOR THE UNITED STATES
DEPARTMENT OF ENERGY

Printed in the United States of America. Available from
National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road, Springfield, Virginia 22161
NTIS price codes—Printed Copy: A03; Microfiche A01

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

ORNL/TM-9976
Dist. Category: UC-70 (Waste)

Engineering Physics and Mathematics Division

A WASTE PACKAGE PERFORMANCE ASSESSMENT CODE WITH AUTOMATED SENSITIVITY-CALCULATION CAPABILITY

B. A. Worley and J. E. Horwedel

Date Published: September 1986

Research sponsored by
U.S. Department of Energy
Office of Nuclear Waste Isolation

Prepared by the
OAK RIDGE NATIONAL LABORATORY
Oak Ridge, Tennessee 37831
operated by
MARTIN MARIETTA ENERGY SYSTEMS, INC.
for the
U.S. DEPARTMENT OF ENERGY
under contract No. DE-AC05-84OR21400

MARTIN MARIETTA ENERGY SYSTEMS LIBRARIES
3 4456 0070881 1

TABLE OF CONTENTS

ABSTRACT v

I. INTRODUCTION 1

II. BACKGROUND 3

III. APPLICATION OF GRESS TO WAPPA 5

IV. SENSITIVITY COMPARISONS WITH RERUNS 7

V. WAPPAG SENSITIVITIES FOR TWO LEACHING PARAMETERS 11

VI. CONCLUSIONS 13

VII. FUTURE WORK 15

REFERENCES 31

ABSTRACT

WAPPA-C is a waste package performance assessment code that predicts the temporal and spatial extent of the loss of containment capability of a given waste package design. This code was enhanced by the addition of the capability to calculate the sensitivity of model results to any parameter. The GRESS automated procedure was used to add this capability in only two man-months of effort. The verification analysis of the enhanced code, WAPPAG, showed that the sensitivities calculated using GRESS were accurate to within the precision of perturbation results against which the sensitivities were compared. Sensitivities of all summary table values to eight diverse data values were verified.

I. INTRODUCTION

WAPPA[1] is a waste package performance assessment code that predicts the temporal and spatial extent of the loss of containment capability of a given waste package design. The code models the problem in a one-dimension radial geometry on timescales up to one million years after isolation. WAPPA has five distinct barrier degredation process models that are driven internally by waste decay and externally be repository stress and fluids. The five process models treat the effects due to radiation, thermal heat removal, mechanical stress, corrosion and leaching. The modelling approach is barrier-integrated and process-sequential. These process models are coupled at the system level by state variables such as source inventory, decay power, temperatures and radionuclide distributions, material property degredations and barrier integrity parameters. The WAPPA code will be used in conjunction with UCBNE10.2,[2] modified to include integrated decay chains, and with BRINETEMP[3] in the overall repository performance assessment. BRINETEMP will be used to calculate brine flow rates and waste package surface temperatures as input to WAPPA. The radionuclide fluxes out of the waste package as calculated in WAPPA will be used as input to UCBNE10.2 to calculate the migration of the radionuclides through the groundwater. The purpose of this paper is to report on the testing and verification of a version of WAPPA that will calculate, at the user's option, the derivative of all responses with respect to any variable used in the code.

II. BACKGROUND

The Office of Nuclear Waste Isolation (ONWI) is responsible for the characterization and performance assessment of candidate high-level waste salt repository sites. Because of the large uncertainties generally associated with the data characterizing geological media and waste behavior and because of the predictive nature of the simulations supporting the assessment, sensitivity and uncertainty analysis are necessary components of the overall performance assessment. To date both statistical and deterministic methods have been used to calculate uncertainties associated with the geological disposal of high-level waste.[4]

Generally, statistical methods are preferred for codes with a moderate number of parameters; direct deterministic methods when there are many performance measures of interest and a moderate number of parameters; and adjoint deterministic methods when there are a limited number of performance measures and a large number of parameters. For large codes with an extensive data base, such as the computer models used by ONWI for performance assessment, the deterministic approaches are more cost efficient for producing a comprehensive ranking of sensitivities of results to data. Both the direct and adjoint perturbation methods, which have been widely used in analyses of nuclear systems,[5] rely on model reruns for calculating first derivatives. The cost of the reruns can be prohibitively expensive depending upon the scope of the analysis and the number of variables of interest. To circumvent this problem, a procedure[6] was developed to make use of computer calculus and the chain rule of differentiation to calculate first derivatives of any model variable with respect to any other model variable. In addition, to avoid the costly programming effort of

implementing this capability in the various codes of interest to ONWI, a Gradient-Enhanced Software System (GRESS)[7] was developed that automatically adds the necessary lines of coding to any FORTRAN source program. GRESS has already been successfully applied to the SWENT, UCBNE10.2, ORIGEN2 and TEMP computer codes.[8,9,10,11] The following sections summarize the application of GRESS to WAPPA and the testing and verification of WAPPAG, the gradient-enhanced version of WAPPA.

III. APPLICATION OF GRESS TO WAPPA

The translation of WAPPA through the GRESS precompiler required about two man-months effort and resulted in the version of WAPPA that has an automated derivative-taking capability, WAPPAG. Most of the effort in translating WAPPA was expended in changing the three-dimensional arrays to two-dimensional arrays and eliminating all doubly argumented variables. These changes were necessary because of the limitations of the current version of GRESS. These limitations will not be present in the next version of GRESS. The testing and verification of the derivative-taking capability of WAPPAG required about one man-month of effort.

WAPPAG has the capability to calculate the first derivative of any variable with respect to any other variable in the code. For most applications, the variables with respect to which the derivatives will be calculated are chosen to be data values of interest. These variables will be referred to as parameters. The variables for which derivatives are calculated with respect to the parameters of interest will be referred to as the responses. In WAPPAG the user has full control over the choice of parameters and responses. In addition to the derivatives, first order sensitivities are also calculated in WAPPAG. The sensitivities, s, are defined by $s = (a/R)/(dR/da)$, where R and a are the reference values of the response and parameter of interest. Defined in this manner, the values of s are normalized sensitivities in the sense that s is equal to the percent change in response R per percent change in a.

IV. SENSITIVITY COMPARISONS WITH RERUNS

The sample problem used in this initial verification is one that accompanied the WAPPA source tape that ORNL had received from ONWI. The problem models the performance of a Commercial High Level Waste (CHLW) borehole concept for the proposed Deaf Smith County repository. The waste canister has a cast steel overpack and is modeled with one glassy waste-form, two metal barriers, two air gaps, two corrosion/oxide layers and one high-MG brine crushed salt backfill.

The responses chosen for comparing sensitivities for this verification study are the masses out of the waste package of the 24 nuclides considered in the sample problem (Summary Table 10 in the WAPPA output). The nuclide distributions are calculated at 260 time steps after initial placement of the wasteform into the repository, but the results are printed for only 52 time steps of interest. The nuclide masses listed in Summary Table 10 of the WAPPA output are the total masses out of the waste package integrated over all the years up to each of the 52 time periods. Sensitivities and gradients for the 10,000 year time period were calculated both by reruns and by WAPPAG for selected data from the various input files. The reference calculated responses are listed in Table 1, which is a copy of Summary Table 10 of the WAPPA output. Comparisons between rerun-calculated sensitivities and GRESS-calculated sensitivities are shown in Tables 2-7.

The first parameter with respect to which sensitivities were calculated was the thermal power source term at the time of burial. This variable, RHEAT(1), is used in the Thermal Model to calculate temperature within the various problem annuli. The temperatures are then used in the Mechanical, Corrosion and Leach models. Thus the sensitivity of the

responses of interest with respect to RHEAT(1) provides a good test for WAPPAG since all but one of the process models are involved. The reference thermal power source at time of burial is 984.3 watts per metric ton of initial heavy metal. The sensitivities of the nuclide masses escaping the waste package boundary 10,000 years after isolation of the waste to the value of RHEAT(1) are listed in Table 2. The sensitivities calculated using WAPPAG are within the calculated precision of the first-order sensitivities estimated from reruns.

The ^{14}C, ^{129}I, ^{135}Cs and ^{137}Cs masses are the most sensitive to the initial decay heat. Note that if the value of RHEAT(1) is changed, in reality the subsequent tabular values of RHEAT input to WAPPA would be changed proportionally. If the sensitivity to initial decay heat is important, the sensitivities to all twenty values of RHEAT would be calculated; but for the purpose of verifying WAPPAG only the sensitivities to RHEAT(1) were calculated.

The second parameter chosen for verification purposes was the height of the wasteform, SHTWP. Although this parameter would not be of real interest in most sensitivity studies, the height directly affects the volume and density of the wasteform and dose rate densities and thus provides a good verification test. The WAPPAG and rerun-calculated sensitivities of the element masses to SHTWP are compared in Table 3 and show excellent agreement. The sensitivities to SHTWP are generally greater than those to RHEAT(1). The ^{99}Tc, ^{126}Sn, Pu and Am nuclides are the most sensitive to the wasteform height.

The third parameter with respect to which sensitivities were calculated was the outside radius of the wasteform. The sensitivities shown

in Table 4 verify that WAPPAG correctly calculated the sensitivities of the nuclide masses to this parameter. All of the sensitivities of the nuclide masses to this radius are greater than the corresponding values with respect to height. This result was anticipated because the problem modelling is one dimensional in the radial direction. Thus the radius affects not only the dose and property densities to a higher order than does the height, but a change in radius affects the analytical solution of the temperature profile.

The gas gap thickness between the metal canister and the overpack for this sample problem is 1.5 cm. The outer radius of the gap, SRTEMP(4), was the fourth parameter examined. The sensitivities of the responses of interest, the nuclide masses escaping the waste package during the first 10,000 years, to a change in the outer radius of this gap were calculated by WAPPAG and reruns. The sensitivities, shown in Table 5, are in good agreement. Except for ^{230}Th, all the mass sensitivities to SRTEMP(4) are opposite in sign compared to the sensitivities to SRTEMP(1). For the heavy elements, an increase in gap thickness decreases their escape from the waste package by about 2 percent for each percent increase in the gap thickness. The ^{14}C, ^{129}I, ^{135}Cs, ^{137}Cs and ^{230}Th are the only nuclides whose sensitivity indicates an increase in mass out of the waste package for an increase in gap thickness. However, at 10,000 years the decrease in the escape of the heavy actinides is more important since the I and Cs radioactivity are very low at that time.

The fifth parameter with respect to which sensitivities were calculated was the ^{233}U mass at 5,000 years. This value, RADTOX(11,13), is datum taken from ORIGEN2 output and input into WAPPA as a member of the

tabulated mass inventories at each of twenty ORIGEN2 time steps. The WAPPAG sensitivities of masses to RADTOX(11,13) are zero, and the rerun-calculated sensitivities for a -1.0% perturbation are also zero as shown in Table 6.

Sensitivities were calculated with respect to a sixth parameter, RGAMA(1), the gamma ray source in photons/sec/MTIHM at time of isolation of the waste. Because the cumulative gamma dose rate does not affect property degradation and radiolysis enhancement factors in the model until a critical dose level is reached, RGAMA(1) had no effect upon the masses out of the waste package. The zero sensitivities in Table 7 confirm this effect and verify that for this test case the arithmetically calculated WAPPAG sensitivities are correct for this parameter.

V. WAPPAG SENSITIVITIES FOR TWO LEACHING PARAMETERS

WAPPA prints fourteen Summary Tables providing various types of information based upon the nuclide concentrations throughout the time period being modelled. For this sample problem there are 24 nuclides and 52 printed time steps, resulting in a total of 17,472 printed values. Sensitivities of these responses to the leach rate coefficient for diffusion of the matrix component, WLRHLF, and to the diffusion coefficient of the representative matrix component in water, WDBULM, were calculated using WAPPAG. Results of directly calculated sensitivities were obtained from perturbations of WLRHLF and WDBULM. Comparison of these sensitivities to the WAPPAG-calculated sensitivities verified that the WAPPAG sensitivities were accurate to within the precision of the directly calculated sensitivities.

VI. CONCLUSIONS

The WAPPA-C waste package performance assessment code was enhanced by the addition of the capability to calculate the sensitivity of model results to any parameter. The GRESS automated procedure was used to add this capability in only two man-months of effort. Another month was expended for testing and verification analysis. The verification analysis showed that the sensitivities calculated using GRESS were accurate to within the precision of the perturbation results against which these sensitivities were compared. The sensitivities for all summary table values were verified.

VII. FUTURE WORK

The GRESS precompiler is presently being updated to handle most all FORTRAN 77 statements and to handle up to seven-dimensional arrays. In addition, work is now underway that will couple the derivatives between the GRESS versions of UCBNE10.2, BRINETEMP and WAPPA. This coupling will provide sensitivities of the responses of interest in an overall performance assessment study to the basic data. A software system is being developed that will automate most of the actual coupling of gradients between the various computer codes.[12]

Another activity that might prove beneficial would be to calculate sensitivities of selected intermediate variables in any of the codes of interest. By careful selection of the intermediate variables for which sensitivities to other variables could be calculated, the effect of different physical process upon the responses of interest could be isolated. For example, consider that the degradation of a material affects the calculation of a variable y that in turn is used in the determination of a response R. The effect of the degradation process can be quantitatively determined by calculating the sensitivity of R with respect to y. Furthermore, if a sensitivity of R with respect to a data value a is calculated, the portion of the sensitivity due to the degradation process can be determined by also calculating the sensitivity of y to a. Even if the physical process is intertwined into the calculation of the response of interest, dummy variables can often be introduced into the equations in such a manner that they multiply any variables effected by the physical process. By then taking out the process of interest and calculating the sensitivity of R with respect to the dummy variable, a quantitative value of the sensitivity of the entire process upon R can be determined.

At some point the sensitivities will be used in conjunction with response surface techniques and/or statistical methods to quantify the overall uncertainties in the performance assessment that arise from use of the computer models. Presently work is being carried out to identify the best way to use the sensitivity data in an uncertainty analysis.

Table 1. Reference Values of Summary Table 10 for Sample Problem

DATE: 25-JAN-80 WPPA PAGE NO. 380
TIME: 06:24:5[illegible] A WASTE PACKAGE PERFORMANCE ASSESSMENT CODE

[illegible] BOREHOLE CONCEPT: 0 YEAR WETTING TIME. 4.000
[illegible] WITH CAST STEEL OVERPACK, 2 METALS, 24 NUCLIDES, 2 AIR GAPS
DEEP SMITH COUNTY CHLW HIGH-MG BRINE CRUSHED SALT BACKFILL 6.000

SUMMARY TABLE # 10

TOTAL ELEMENT MASS OUT AT WASTE PACKAGE BOUNDARY (GRAMS)

TIME SINCE EMPLACEMENT (YEARS)

ELEMENT	5.0	10.0	15.0	20.0	25.0	30.0	35.0	45.0
C	0.64561E+02	0.12453E+03	0.15737E+03	0.17493E+03	0.18513E+03	0.19117E+03	0.19507E+03	0.19950E+03
Se	0.66526E-03	0.11511E-01	0.16255E-01	0.20163E-01	0.23814E-01	0.27313E-01	0.30718E-01	0.37360E-01
Sr	0.5[illegible]E+01	[illegible]	[illegible]	0.15731E+02	0.18432E+02	0.20897E+02	0.23143E+02	0.26949E+02
Tc	0.66347E-02	0.11145E-01	0.16260E-01	0.20171E-01	0.23825E-01	0.27330E-01	0.30743E-01	0.37414E-01
Sn	0.66347E-03	0.11[illegible]E-02	0.16260E-02	0.20171E-02	0.23825E-02	0.27330E-02	0.30743E-02	0.37414E-02
I	0.92294E+02	0.15[illegible]E+03	0.22468E+03	0.24939E+03	0.26368E+03	0.27212E+03	0.27755E+03	0.28373E+03
Cs	[illegible]	0.17[illegible]E+04	0.21427E+04	0.23592E+04	0.24806E+04	0.25504E+04	0.25942E+04	0.26419E+04
Cs	[illegible]	[illegible]	[illegible]E+04	0.23592E+04	0.24806E+04	0.25504E+04	0.25942E+04	0.26419E+04
Ra	[illegible]	[illegible]	0.76524E-06	0.91560E-06	0.10168E-05	0.10847E-05	0.11343E-05	0.12029E-05
[illegible]	0.21[illegible]	[illegible]	0.51525E-02	0.52525E-02	0.62856E-02	0.65547E-02	0.67330E-02	0.69409E-02
U	0.66348E-02	0.11514E-01	0.16260E-01	0.20171E-01	0.23825E-01	0.27331E-01	0.30744E-01	0.37417E-01
U	0.66842E-02	0.11514E-01	0.16260E-01	0.20171E-01	0.23825E-01	0.27331E-01	0.30744E-01	0.37417E-01
U	0.66848E-02	0.11514E-01	0.16260E-01	0.20171E-01	0.23825E-01	0.27331E-01	0.30744E-01	0.37417E-01
Np	0.66846E-02	0.11514E-01	0.16260E-01	0.20170E-01	0.23824E-01	0.27329E-01	0.30741E-01	0.37411E-01
Pu	0.66822E-02	0.11510E-01	0.16254E-01	0.20162E-01	0.23812E-01	0.27310E-01	0.30714E-01	0.37355E-01
Pu	0.66322E-02	0.11510E-01	0.16254E-01	0.20162E-01	0.23812E-01	0.27310E-01	0.30714E-01	0.37355E-01
Pu	0.66822E-02	0.11510E-01	0.16254E-01	0.20162E-01	0.23812E-01	0.27310E-01	0.30714E-01	0.37355E-01
Pu	0.66822E-02	0.11510E-01	0.16254E-01	0.20162E-01	0.23812E-01	0.27310E-01	0.30714E-01	0.37355E-01
Pu	0.66822E-02	0.11510E-01	0.16254E-01	0.20162E-01	0.23812E-01	0.27310E-01	0.30714E-01	0.37355E-01
Pu	0.66822E-02	0.11510E-01	0.16254E-01	0.20162E-01	0.23812E-01	0.27310E-01	0.30714E-01	0.37355E-01
Am	0.66648E-03	0.11514E-02	0.16260E-02	0.20171E-02	0.23825E-02	0.27331E-02	0.30744E-02	0.37417E-02
Am	0.66846E-03	0.11514E-02	0.16260E-02	0.20171E-02	0.23825E-02	0.27331E-02	0.30744E-02	0.37417E-02
Cm	0.66772E-02	0.11501E-01	0.16237E-01	0.20132E-01	0.23757E-01	0.27210E-01	0.30536E-01	0.36829E-01
Cm	0.66772E-02	0.11501E-01	0.16237E-01	0.20132E-01	0.23757E-01	0.27210E-01	0.30536E-01	0.36829E-01
MATRIX	0.57957E+06	0.11[illegible]E+07	0.14[illegible]E+07	0.15722E+07	0.16652E+07	0.17254E+07	0.17626E+07	0.18049E+07

STNUCW(I,ITM1)=SNUCWT(I) SNUCWT(I)=SNUCWT(I) +SNUCWP(I)*DELTAT
STNUCWM(ITM1)=PRESTNUCWM*WLFLAM*DELTAT PRESTNUCWM=STNUCWM(ITM1-1)

Table 1 (Continued)

DATE: 23-JAN-80 WAPPA PAGE NO. 381
TIME: 08:24:38 A WASTE PACKAGE PERFORMANCE ASSESSMENT CODE

CHLW BOREHOLE CONCEPT: 0 YEAR WETTING TIME. 4.000
CANISTER WITH CAST STEEL OVERPACK, 2 METALS, 24 NUCLIDES, 2 AIR GAPS
DEAF SMITH COUNTY CHLW HIGH-MG BRINE CRUSHED SALT BACKFILL 6.000

SUMMARY TABLE # 10

TOTAL ELEMENT MASS OUT AT WASTE PACKAGE BOUNDARY (GRAMS)

TIME SINCE EMPLACEMENT (YEARS)

ELEMENT	55.0	65.0	75.0	95.0	125.0	150.0	175.0	200.0
C	0.20192E+03	0.20341E+03	0.20440E+03	0.20552E+03	0.20644E+03	0.20699E+03	0.20742E+03	0.20776E+03
Se	0.43852E-01	0.50239E-01	0.56540E-01	0.68877E-01	0.86800E-01	0.10135E+00	0.11554E+00	0.12935E+00
Sr	0.29905E+02	0.32173E+02	0.33881E+02	0.36038E+02	0.37882E+02	0.39006E+02	0.39874E+02	0.40560E+02
Tc	0.43955E-01	0.50420E-01	0.56835E-01	0.69572E-01	0.88529E-01	0.10423E+00	0.11985E+00	0.13541E+00
Sn	0.43956E-02	0.50422E-02	0.56839E-02	0.69580E-02	0.88549E-02	0.10426E-01	0.11990E-01	0.13548E-01
I	0.28710E+03	0.28918E+03	0.29055E+03	0.29211E+03	0.29339E+03	0.29416E+03	0.29476E+03	0.29523E+03
Cs	0.26667E+04	0.26816E+04	0.26911E+04	0.27016E+04	0.27098E+04	0.27147E+04	0.27184E+04	0.27214E+04
Cs	0.26667E+04	0.26816E+04	0.26911E+04	0.27016E+04	0.27098E+04	0.27147E+04	0.27184E+04	0.27214E+04
Ra	0.12502E-05	0.12838E-05	0.13089E-05	0.13438E-05	0.13809E-05	0.14076E-05	0.14320E-05	0.14551E-05
Th	0.70563E-02	0.71284E-02	0.71764E-02	0.72318E-02	0.72777E-02	0.73059E-02	0.73280E-02	0.73458E-02
U	0.43962E-01	0.50432E-01	0.56855E-01	0.69619E-01	0.88649E-01	0.10443E+00	0.12016E+00	0.13585E+00
U	0.43962E-01	0.50432E-01	0.56855E-01	0.69619E-01	0.88649E-01	0.10443E+00	0.12016E+00	0.13585E+00
U	0.43962E-01	0.50432E-01	0.56855E-01	0.69619E-01	0.88649E-01	0.10443E+00	0.12016E+00	0.13585E+00
Np	0.43950E-01	0.50411E-01	0.56822E-01	0.69542E-01	0.88458E-01	0.10412E+00	0.11969E+00	0.13520E+00
Pu	0.43844E-01	0.50228E-01	0.56524E-01	0.68852E-01	0.86762E-01	0.10130E+00	0.11548E+00	0.12928E+00
Pu	0.43844E-01	0.50228E-01	0.56524E-01	0.68852E-01	0.86762E-01	0.10130E+00	0.11548E+00	0.12928E+00
Pu	0.43844E-01	0.50228E-01	0.56524E-01	0.68852E-01	0.86762E-01	0.10130E+00	0.11548E+00	0.12928E+00
Pu	0.43844E-01	0.50228E-01	0.56524E-01	0.68852E-01	0.86762E-01	0.10130E+00	0.11548E+00	0.12928E+00
Pu	0.43844E-01	0.50228E-01	0.56524E-01	0.68852E-01	0.86762E-01	0.10130E+00	0.11548E+00	0.12928E+00
Pu	0.43844E-01	0.50228E-01	0.56524E-01	0.68852E-01	0.86762E-01	0.10130E+00	0.11548E+00	0.12928E+00
Am	0.43962E-02	0.50432E-02	0.56855E-02	0.69620E-02	0.88650E-02	0.10443E-01	0.12016E-01	0.13585E-01
Am	0.43962E-02	0.50432E-02	0.56855E-02	0.69620E-02	0.88650E-02	0.10443E-01	0.12016E-01	0.13585E-01
Cm	0.42560E-01	0.47635E-01	0.51921E-01	0.57772E-01	0.62702E-01	0.65678E-01	0.67914E-01	0.69617E-01
Cm	0.42560E-01	0.47635E-01	0.51921E-01	0.57772E-01	0.62702E-01	0.65678E-01	0.67914E-01	0.69617E-01
MATRIX	0.18281E+07	0.18424E+07	0.18518E+07	0.18626E+07	0.18714E+07	0.18767E+07	0.18809E+07	0.18841E+07

STNUCW(I,ITM1)=SNUCWT(I) SNUCWT(I)=SNUCWT(I) +SNUCWP(I)*DELTAT
STNUCWM(ITM1)=PRSTNUCWM+WLFLXM*DELTAT PRSTNUCWM=STNUCWM(ITM1-1)

Table 1 (Continued)

DATE: 23-JAN-86
TIME: 08:24:38

WAPPA
A WASTE PACKAGE PERFORMANCE ASSESSMENT CODE

PAGE NO. 382

CHLW BOREHOLE CONCEPT: 0 YEAR WETTING TIME. 4.000
CANISTER WITH CAST STEEL OVERPACK, 2 METALS, 24 NUCLIDES, 2 AIR GAPS
DEAF SMITH COUNTY CHLW HIGH-MG BRINE CRUSHED SALT BACKFILL 6.000

SUMMARY TABLE # 10

TOTAL ELEMENT MASS OUT AT WASTE PACKAGE BOUNDARY (GRAMS)

TIME SINCE EMPLACEMENT (YEARS)

ELEMENT	225.0	250.0	275.0	300.0	350.0	400.0	450.0	500.0
C	0.20805E+03	0.20830E+03	0.20852E+03	0.20871E+03	0.20904E+03	0.20931E+03	0.20954E+03	0.20973E+03
Se	0.14233E+00	0.15601E+00	0.16889E+00	0.18148E+00	0.20575E+00	0.22890E+00	0.25097E+00	0.27200E+00
Sr	0.41135E+02	0.41637E+02	0.42080E+02	0.42475E+02	0.43143E+02	0.43696E+02	0.44163E+02	0.44563E+02
Tc	0.15091E+00	0.16636E+00	0.18175E+00	0.19710E+00	0.22765E+00	0.25802E+00	0.28820E+00	0.31820E+00
Sn	0.15101E-01	0.16649E-01	0.18192E-01	0.19730E-01	0.22794E-01	0.25841E-01	0.28872E-01	0.31886E-01
I	0.29563E+03	0.29598E+03	0.29628E+03	0.29655E+03	0.29701E+03	0.29738E+03	0.29770E+03	0.29797E+03
Cs	0.27235E+04	0.27259E+04	0.27278E+04	0.27294E+04	0.27322E+04	0.27345E+04	0.27364E+04	0.27381E+04
Cs	0.27236E+04	0.27259E+04	0.27278E+04	0.27294E+04	0.27322E+04	0.27345E+04	0.27364E+04	0.27381E+04
Ra	0.14768E-05	0.14971E-05	0.15165E-05	0.15350E-05	0.15705E-05	0.16047E-05	0.16384E-05	0.16721E-05
Th	0.73611E-02	0.73745E-02	0.73865E-02	0.73973E-02	0.74160E-02	0.74320E-02	0.74458E-02	0.74581E-02
U	0.15151E+00	0.16713E+00	0.18273E+00	0.19830E+00	0.22939E+00	0.26039E+00	0.29133E+00	0.32220E+00
U	0.15151E+00	0.16713E+00	0.18273E+00	0.19830E+00	0.22939E+00	0.26039E+00	0.29133E+00	0.32220E+00
U	0.15151E+00	0.16713E+00	0.18273E+00	0.19830E+00	0.22939E+00	0.26039E+00	0.29133E+00	0.32220E+00
Np	0.15064E+00	0.16602E+00	0.18136E+00	0.19664E+00	0.22706E+00	0.25730E+00	0.28736E+00	0.31727E+00
Pu	0.14276E+00	0.15593E+00	0.16882E+00	0.18142E+00	0.20571E+00	0.22891E+00	0.25105E+00	0.27217E+00
Pu	0.14276E+00	0.15593E+00	0.16882E+00	0.18142E+00	0.20571E+00	0.22891E+00	0.25105E+00	0.27217E+00
Pu	0.14276E+00	0.15593E+00	0.16882E+00	0.18142E+00	0.20571E+00	0.22891E+00	0.25105E+00	0.27217E+00
Pu	0.14276E+00	0.15593E+00	0.16882E+00	0.18142E+00	0.20571E+00	0.22891E+00	0.25105E+00	0.27217E+00
Pu	0.14276E+00	0.15593E+00	0.16882E+00	0.18142E+00	0.20571E+00	0.22891E+00	0.25105E+00	0.27217E+00
Pu	0.14276E+00	0.15593E+00	0.16882E+00	0.18142E+00	0.20571E+00	0.22891E+00	0.25105E+00	0.27217E+00
Pu	0.14276E+00	0.15593E+00	0.16882E+00	0.18142E+00	0.20571E+00	0.22891E+00	0.25105E+00	0.27217E+00
Am	0.15150E-01	0.16712E-01	0.18271E-01	0.19828E-01	0.22933E-01	0.26029E-01	0.29116E-01	0.32194E-01
Am	0.15150E-01	0.16712E-01	0.18271E-01	0.19828E-01	0.22933E-01	0.26029E-01	0.29116E-01	0.32194E-01
Cm	0.71023E-01	0.72254E-01	0.73343E-01	0.74315E-01	0.75963E-01	0.77327E-01	0.78477E-01	0.79461E-01
Cm	0.71023E-01	0.72254E-01	0.73343E-01	0.74315E-01	0.75963E-01	0.77327E-01	0.78477E-01	0.79461E-01
MATRIX	0.18869E+07	0.18893E+07	0.18914E+07	0.18932E+07	0.18964E+07	0.18990E+07	0.19012E+07	0.19030E+07

STNUCW(I,ITM1)=SNUCWT(I) SNUCWT(I)=SNUCWT(I) +SNUCWP(I)*DELTAT
STNUCWM(ITM1)=PRSTNUCWM*WLPLXM*DELTAT PRSTNUCWM=STNUCWM(ITM1-1)

Table 1 (Continued)

DATE: 23-JAN-86 WAPPA PAGE NO. 383
TIME: 08:24:38 A WASTE PACKAGE PERFORMANCE ASSESSMENT CODE

CHLW BOREHOLE CONCEPT: 0 YEAR WETTING TIME. 4.000
CANISTER WITH CAST STEEL OVERPACK, 2 METALS, 24 NUCLIDES, 2 AIR GAPS
DEAF SMITH COUNTY CHLW HIGH-MG BRINE CRUSHED SALT BACKFILL 6.000

SUMMARY TABLE # 10

TOTAL ELEMENT MASS OUT AT WASTE PACKAGE BOUNDARY (GRAMS)

TIME SINCE EMPLACEMENT (YEARS)

ELEMENT	575.0	650.0	725.0	800.0	850.0	900.0	950.0	1000.0
C	0.20997E+03	0.21017E+03	0.21033E+03	0.21046E+03	0.21054E+03	0.21061E+03	0.21068E+03	0.21074E+03
Se	0.30145E+00	0.32853E+00	0.35345E+00	0.37638E+00	0.39069E+00	0.40425E+00	0.41711E+00	0.42931E+00
Sr	0.45057E+02	0.45457E+02	0.45790E+02	0.46071E+02	0.46236E+02	0.46386E+02	0.46522E+02	0.46647E+02
Tc	0.36281E+00	0.40695E+00	0.45059E+00	0.49371E+00	0.52218E+00	0.55041E+00	0.57839E+00	0.60612E+00
Sn	0.36373E-01	0.40818E-01	0.45218E-01	0.49574E-01	0.52452E-01	0.55309E-01	0.58145E-01	0.60958E-01
I	0.29850E+03	0.29858E+03	0.29860E+03	0.29899E+03	0.29910E+03	0.29920E+03	0.29929E+03	0.29938E+03
Cs	0.27401E+04	0.27418E+04	0.27431E+04	0.27443E+04	0.27449E+04	0.27456E+04	0.27461E+04	0.27466E+04
Cs	0.27401E+04	0.27418E+04	0.27431E+04	0.27443E+04	0.27449E+04	0.27456E+04	0.27461E+04	0.27466E+04
Ra	0.17194E-05	0.17623E-05	0.18022E-05	0.18399E-05	0.18642E-05	0.18880E-05	0.19114E-05	0.19345E-05
Th	0.74737E-02	0.74870E-02	0.74984E-02	0.75085E-02	0.75146E-02	0.75203E-02	0.75257E-02	0.75307E-02
U	0.36840E+00	0.41446E+00	0.46039E+00	0.50619E+00	0.53666E+00	0.56707E+00	0.59743E+00	0.62773E+00
U	0.36840E+00	0.41446E+00	0.46039E+00	0.50619E+00	0.53666E+00	0.56707E+00	0.59743E+00	0.62773E+00
U	0.36840E+00	0.41446E+00	0.46039E+00	0.50619E+00	0.53666E+00	0.56707E+00	0.59743E+00	0.62773E+00
Np	0.36177E+00	0.40582E+00	0.44943E+00	0.49258E+00	0.52112E+00	0.54945E+00	0.57759E+00	0.60553E+00
Pu	0.30181E+00	0.32915E+00	0.35437E+00	0.37767E+00	0.39226E+00	0.40611E+00	0.41928E+00	0.43181E+00
Pu	0.30181E+00	0.32915E+00	0.35437E+00	0.37767E+00	0.39226E+00	0.40611E+00	0.41928E+00	0.43181E+00
Pu	0.30181E+00	0.32915E+00	0.35437E+00	0.37767E+00	0.39226E+00	0.40611E+00	0.41928E+00	0.43181E+00
Pu	0.30181E+00	0.32915E+00	0.35437E+00	0.37767E+00	0.39226E+00	0.40611E+00	0.41928E+00	0.43181E+00
Pu	0.30181E+00	0.32915E+00	0.35437E+00	0.37767E+00	0.39226E+00	0.40611E+00	0.41928E+00	0.43181E+00
Pu	0.30181E+00	0.32915E+00	0.35437E+00	0.37767E+00	0.39226E+00	0.40611E+00	0.41928E+00	0.43181E+00
Am	0.36792E-01	0.41367E-01	0.45916E-01	0.50436E-01	0.53432E-01	0.56411E-01	0.59373E-01	0.62316E-01
Am	0.36792E-01	0.41367E-01	0.45916E-01	0.50436E-01	0.53432E-01	0.56411E-01	0.59373E-01	0.62316E-01
Cm	0.80673E-01	0.81653E-01	0.82461E-01	0.83140E-01	0.83538E-01	0.83897E-01	0.84223E-01	0.84521E-01
Cm	0.80673E-01	0.81653E-01	0.82461E-01	0.83140E-01	0.83538E-01	0.83897E-01	0.84223E-01	0.84521E-01
MATRIX	0.19053E+07	0.19072E+07	0.19085E+07	0.19101E+07	0.19108E+07	0.19115E+07	0.19122E+07	0.19127E+07

STNUCW(I,ITM1)=SNUCWT(I) SNUCWT(I)=SNUCWT(I) +SNUCWP(I)*DELTAT
STNUCWM(ITM1)=PRSTNUCWM*WLFLXM*DELTAT PRSTNUCWM=STNUCWM(ITM1-1)

Table 1 (Continued)

DATE: 23-JAN-86 WAPPA PAGE NO. 384
TIME: 08:24:35 A WASTE PACKAGE PERFORMANCE ASSESSMENT CODE

CHLW BOREHOLE CONCEPT: 0 YEAR WETTING TIME. 4.000
CANISTER WITH CAST STEEL OVERPACK, 2 METALS, 24 NUCLIDES, 2 AIR GAPS
DEAF SMITH COUNTY CHLW HIGH-MG BRINE CRUSHED SALT BACKFILL 6.000

SUMMARY TABLE # 10

TOTAL ELEMENT MASS OUT AT WASTE PACKAGE BOUNDARY (GRAMS)

TIME SINCE EMPLACEMENT (YEARS)

ELEMENT	1050.0	1100.0	1150.0	1200.0	1400.0	1600.0	1800.0	2000.0
C	0.21060E+03	0.21055E+03	0.21090E+03	0.21095E+03	0.21111E+03	0.21126E+03	0.21138E+03	0.21148E+03
Sa	0.44099E+00	0.45227E+00	0.46316E+00	0.47369E+00	0.51213E+00	0.54611E+00	0.57642E+00	0.60365E+00
Sr	0.46704E+02	0.46874E+02	0.45979E+02	0.47078E+02	0.47425E+02	0.47717E+02	0.47967E+02	0.48185E+02
Tc	0.63365E+00	0.66100E+00	0.68817E+00	0.71516E+00	0.82115E+00	0.92433E+00	0.10247E+01	0.11224E+01
Sn	0.63753E-01	0.66533E-01	0.69296E-01	0.72043E-01	0.82855E-01	0.93414E-01	0.10372E+00	0.11378E+00
I	0.29943E+03	0.29953E+03	0.29960E+03	0.29966E+03	0.29990E+03	0.30009E+03	0.30026E+03	0.30041E+03
Cs	0.27471E+04	0.27475E+04	0.27480E+04	0.27484E+04	0.27498E+04	0.27510E+04	0.27520E+04	0.27529E+04
Cs	0.27471E+04	0.27475E+04	0.27480E+04	0.27484E+04	0.27498E+04	0.27510E+04	0.27520E+04	0.27529E+04
Ra	0.19573E-05	0.19797E-05	0.20018E-05	0.20237E-05	0.21095E-05	0.21945E-05	0.22803E-05	0.23682E-05
Th	0.75356E-02	0.75402E-02	0.75448E-02	0.75491E-02	0.75655E-02	0.75805E-02	0.75945E-02	0.76079E-02
U	0.65796E+00	0.68819E+00	0.71835E+00	0.74848E+00	0.86852E+00	0.98788E+00	0.11066E+01	0.12246E+01
U	0.65798E+00	0.68819E+00	0.71835E+00	0.74848E+00	0.86852E+00	0.98788E+00	0.11066E+01	0.12246E+01
U	0.65798E+00	0.68819E+00	0.71835E+00	0.74848E+00	0.86852E+00	0.98788E+00	0.11066E+01	0.12246E+01
Np	0.63330E+00	0.66092E+00	0.68836E+00	0.71570E+00	0.82329E+00	0.92855E+00	0.10316E+01	0.11324E+01
Pu	0.44365E+00	0.45549E+00	0.46676E+00	0.47767E+00	0.51781E+00	0.55365E+00	0.58595E+00	0.61527E+00
Pu	0.44365E+00	0.45549E+00	0.46676E+00	0.47767E+00	0.51781E+00	0.55365E+00	0.58595E+00	0.61527E+00
Pu	0.44365E+00	0.45549E+00	0.46676E+00	0.47767E+00	0.51781E+00	0.55365E+00	0.58595E+00	0.61527E+00
Pu	0.44365E+00	0.45549E+00	0.46676E+00	0.47767E+00	0.51781E+00	0.55365E+00	0.58595E+00	0.61527E+00
Pu	0.44365E+00	0.45549E+00	0.46676E+00	0.47767E+00	0.51781E+00	0.55365E+00	0.58595E+00	0.61527E+00
Pu	0.44365E+00	0.45549E+00	0.46676E+00	0.47767E+00	0.51781E+00	0.55365E+00	0.58595E+00	0.61527E+00
Am	0.65243E-01	0.68154E-01	0.71050E-01	0.73930E-01	0.85248E-01	0.96236E-01	0.10684E+00	0.11699E+00
Am	0.65243E-01	0.68154E-01	0.71050E-01	0.73930E-01	0.85248E-01	0.96236E-01	0.10684E+00	0.11699E+00
Cm	0.84797E-01	0.85058E-01	0.85304E-01	0.85536E-01	0.86340E-01	0.87004E-01	0.87563E-01	0.88042E-01
Cm	0.84797E-01	0.85058E-01	0.85304E-01	0.85536E-01	0.86340E-01	0.87004E-01	0.87563E-01	0.88042E-01
MATRIX	0.19133E+07	0.19136E+07	0.19140E+07	0.19147E+07	0.19163E+07	0.19177E+07	0.19188E+07	0.19198E+07

STNUCW(I,ITM1)=SNUCWT(I) SNUCWT(I)=SNUCWT(I) +SNUCWP(I)*DELTAT
STNUCWM(ITM1)=PRSTNUCWM*WLF(XN*DELTAT) TNUCWM=STNUCWM(ITM1-1)

Table 1 (Continued)

DATE: 25-JAN-86
TIME: 06:24:58

WAPPA
A WASTE PACKAGE PERFORMANCE ASSESSMENT CODE

PAGE NO. 385

CHLW BOREHOLE CONCEPT: 0 YEAR WETTING TIME. 4.000
CANISTER WITH CAST STEEL OVERPACK, 2 METALS, 24 NUCLIDES, 2 AIR GAPS
DEAF SMITH COUNTY CHLW HIGH-MG BRINE CRUSHED SALT BACKFILL 6.000

SUMMARY TABLE # 10

TOTAL ELEMENT MASS OUT AT WASTE PACKAGE BOUNDARY (GRAMS)

TIME SINCE EMPLACEMENT (YEARS)

ELEMENT	2250.0	2500.0	2750.0	3000.0	3500.0	4000.0	4500.0	5000.0
C	0.21160E+03	0.21170E+03	0.21179E+03	0.21188E+03	0.21203E+03	0.21216E+03	0.21227E+03	0.21237E+03
Se	0.63451E+00	0.66274E+00	0.68673E+00	0.71280E+00	0.75582E+00	0.79367E+00	0.82739E+00	0.85774E+00
Sr	0.48425E+02	0.42641E+02	0.48636E+02	0.49013E+02	0.49326E+02	0.49595E+02	0.49832E+02	0.50042E+02
Tc	0.12412E+01	0.13608E+01	0.14695E+01	0.15793E+01	0.17904E+01	0.19913E+01	0.21829E+01	0.23658E+01
Sn	0.12605E+00	0.13804E+00	0.14975E+00	0.16120E+00	0.18328E+00	0.20442E+00	0.22467E+00	0.24410E+00
I	0.30057E+03	0.30071E+03	0.30084E+03	0.30096E+03	0.30117E+03	0.30135E+03	0.30151E+03	0.30165E+03
Cs	0.27539E+04	0.27547E+04	0.27555E+04	0.27562E+04	0.27575E+04	0.27586E+04	0.27596E+04	0.27604E+04
Cs	0.27539E+04	0.27547E+04	0.27555E+04	0.27562E+04	0.27575E+04	0.27586E+04	0.27596E+04	0.27604E+04
Ra	0.24779E-05	0.25856E-05	0.26929E-05	0.28003E-05	0.30187E-05	0.32459E-05	0.34864E-05	0.37441E-05
Th	0.76239E-02	0.76393E-02	0.76543E-02	0.76689E-02	0.76977E-02	0.77263E-02	0.77553E-02	0.77851E-02
U	0.13712E+01	0.15170E+01	0.16620E+01	0.18061E+01	0.20919E+01	0.23745E+01	0.26539E+01	0.29303E+01
U	0.13712E+01	0.15170E+01	0.16620E+01	0.18061E+01	0.20919E+01	0.23745E+01	0.26539E+01	0.29303E+01
U	0.13712E+01	0.15170E+01	0.16620E+01	0.18061E+01	0.20919E+01	0.23745E+01	0.26539E+01	0.29303E+01
Np	0.12557E+01	0.13763E+01	0.14942E+01	0.16095E+01	0.18324E+01	0.20463E+01	0.22517E+01	0.24493E+01
Pu	0.64863E+00	0.67981E+00	0.70859E+00	0.73548E+00	0.78424E+00	0.82793E+00	0.86756E+00	0.90388E+00
Pu	0.64863E+00	0.67981E+00	0.70859E+00	0.73548E+00	0.78424E+00	0.82793E+00	0.86756E+00	0.90388E+00
Pu	0.64863E+00	0.67981E+00	0.70859E+00	0.73548E+00	0.78424E+00	0.82793E+00	0.86756E+00	0.90388E+00
Pu	0.64863E+00	0.67981E+00	0.70859E+00	0.73548E+00	0.78424E+00	0.82793E+00	0.86756E+00	0.90388E+00
Pu	0.64863E+00	0.67981E+00	0.70859E+00	0.73548E+00	0.78424E+00	0.82793E+00	0.86756E+00	0.90388E+00
Pu	0.64863E+00	0.67981E+00	0.70859E+00	0.73548E+00	0.78424E+00	0.82793E+00	0.86756E+00	0.90388E+00
Am	0.12919E+00	0.14099E+00	0.15239E+00	0.16335E+00	0.18396E+00	0.20292E+00	0.22026E+00	0.23603E+00
Am	0.12919E+00	0.14099E+00	0.15239E+00	0.16335E+00	0.18396E+00	0.20292E+00	0.22026E+00	0.23603E+00
Cm	0.88560E-01	0.89015E-01	0.89417E-01	0.89777E-01	0.90386E-01	0.90890E-01	0.91314E-01	0.91675E-01
Cm	0.88560E-01	0.89015E-01	0.89417E-01	0.89777E-01	0.90386E-01	0.90890E-01	0.91314E-01	0.91675E-01
MATRIX	0.19210E+07	0.19219E+07	0.19228E+07	0.19237E+07	0.19251E+07	0.19263E+07	0.19274E+07	0.19284E+07

STNUCW(I,ITM1)=SNUCWT(I) SNUCWT(I)=SNUCWT(I) +SNUCWP(I)*DELTAT
STNUCWM(ITM1)=PRSTNUCWM*NLFLA[illegible]ELTAT PRSTN[illegible]STNUCW(ITM1-1)

Table 1 (Continued)

DATE: 23-JAN-86 WAPPA PAGE NO. 386
TIME: [illegible]
A WASTE PACKAGE PERFORMANCE ASSESSMENT CODE

CHLW BOREHOLE CONCEPT: 0 YEAR WETTING TIME. 4.000
CANISTER WITH CAST STEEL OVERPACK, 2 METALS, 24 NUCLIDES, 2 AIR GAPS
DEAF SMITH COUNTY CHLW HIGH-MG BRINE CRUSHED SALT BACKFILL 6.000

SUMMARY TABLE # 10

TOTAL ELEMENT MASS OUT AT WASTE PACKAGE BOUNDARY (GRAMS)

TIME SINCE EMPLACEMENT (YEARS)

ELEMENT	6250.0	7500.0	8750.0	10000.0
C	0.21260E+03	0.21282E+03	0.21302E+03	0.21321E+03
Se	0.92730E+00	0.99237E+00	0.10540E+01	0.11128E+01
Sr	0.50521E+02	0.50967E+02	0.51387E+02	0.51787E+02
Tc	0.28048E+01	0.32293E+01	0.36419E+01	0.40439E+01
Sn	0.29090E+00	0.33632E+00	0.38059E+00	0.42384E+00
I	0.30197E+03	0.30227E+03	0.30255E+03	0.30281E+03
Cs	0.27624E+04	0.27642E+04	0.27659E+04	0.27675E+04
Cs	0.27624E+04	0.27642E+04	0.27659E+04	0.27675E+04
Ra	0.44560E-05	0.52647E-05	0.61964E-05	0.72772E-05
Th	0.78659E-02	0.79580E-02	0.80644E-02	0.81881E-02
U	0.36142E+01	0.42921E+01	0.49650E+01	0.56331E+01
U	0.36142E+01	0.42921E+01	0.49650E+01	0.56331E+01
U	0.36142E+01	0.42921E+01	0.49650E+01	0.56331E+01
Np	0.29264E+01	0.33901E+01	0.38429E+01	0.42860E+01
Pu	0.98858E+00	0.10691E+01	0.11467E+01	0.12218E+01
Pu	0.98858E+00	0.10691E+01	0.11467E+01	0.12218E+01
Pu	0.98858E+00	0.10691E+01	0.11467E+01	0.12218E+01
Pu	0.98858E+00	0.10691E+01	0.11467E+01	0.12218E+01
Pu	0.98858E+00	0.10691E+01	0.11467E+01	0.12218E+01
Pu	0.98858E+00	0.10691E+01	0.11467E+01	0.12218E+01
Am	0.27161E+00	0.30361E+00	0.33239E+00	0.35820E+00
Am	0.27161E+00	0.30361E+00	0.33239E+00	0.35820E+00
Cm	0.92432E-01	0.93064E-01	0.93601E-01	0.94059E-01
Cm	0.92432E-01	0.93064E-01	0.93601E-01	0.94059E-01
MATRIX	0.19306E+07	0.19327E+07	0.19346E+07	0.19365E+07

STNUCW(I,ITM1)=SNUCWT(I) SNUCWT(I)=SNUCWT(I) +SNUCWP(I)*DELTAT
STNUCWM(ITM1)=PRSTNUCWM*WLFLXM*DELTA PRSTNUCWM=STNUCWM(ITM1-1)

Table 2. Comparison of WAPPAG and Directly Calculated Sensitivities to Thermal Power at Time of Burial

Rerun perturbation, %	-0.944833E+00
Parameter value, W/MTIHM	0.984300E+03
Parameter name	RHEAT(1)

NUCLIDE	SENSITIVITY (WAPPAG)	SENSITIVITY (RERUN)	MASS OUT AFTER 10,000 YEARS
C 14	-0.139775E+01	-0.141480E+01	0.213209E+03
Se 79	-0.126189E+00	-0.122580E+00	0.111276E+01
Sr 90	-0.245947E-01	-0.210575E-01	0.517873E+02
Tc 99	0.158648E+00	0.163489E+00	0.404388E+01
Sn 126	0.182543E-00	0.187391E+00	0.423839E+00
I 129	-0.144410E+01	-0.146271E+01	0.302813E+03
Cs 135	-0.149290E+01	-0.151266E+01	0.276751E+04
Cs 137	-0.149290E+01	-0.151266E+01	0.276751E+04
Ra 226	-0.601444E+00	-0.602368E+00	0.727716E-05
Th 230	-0.845911E+00	-0.849164E+00	0.818810E-02
U 233	0.369588E+00	0.374087E+00	0.563315E+01
U 234	0.369588E+00	0.374087E+00	0.563315E+01
U 238	0.369588E+00	0.374087E+00	0.563315E+01
Np 237	0.187171E+00	0.192005E+00	0.428599E+01
Pu 238	-0.134674E+00	-0.131020E+00	0.122183E+01
Pu 239	-0.134674E+00	-0.131020E+00	0.122183E+01
Pu 240	-0.134674E+00	-0.131020E+00	0.122183E+01
Pu 241	-0.134674E+00	-0.131020E+00	0.122183E+01
Pu 242	-0.134674E+00	-0.131020E+00	0.122183E+01
Pu 244	-0.134674E+00	-0.131020E+00	0.122183E+01
Am 241	0.136951E+00	0.141553E+00	0.358202E+00
Am 243	0.136951E+00	0.141553E+00	0.358202E+00
Cm 244	0.125190E-01	0.160715E-01	0.940592E-01
Cm 245	0.125190E-01	0.160715E-01	0.940592E-01

Table 3. Comparison of WAPPAG and Directly Calculated Sensitivities to the Wasteform Height

Rerun perturbation	0.999998E+00
Parameter value, m	0.370000E+01
Parameter name	SHTWP

NUCLIDE	SENSITIVITY (WAPPAG)	SENSITIVITY (RERUN)	MASS OUT AFTER 10,000 YEARS
C 14	-0.374480E+00	-0.370955E+00	0.213209E+03
Se 79	0.845037E+00	0.842392E+00	0.111276E+01
Sr 90	0.955058E+00	0.951906E+00	0.517873E+02
Tc 99	0.113061E+01	0.112917E+01	0.404388E+01
Sn 126	0.115462E+01	0.115326E+01	0.423839E+00
I 129	-0.420103E+00	-0.415598E+00	0.302813E+03
Cs 135	-0.467530E+00	-0.462265E+00	0.276751E+04
Cs 137	-0.467530E+00	-0.462265E+00	0.276751E+04
Ra 226	0.376438E+00	0.376176E+00	0.727716E-05
Th 230	0.163473E+00	0.159067E+00	0.818810E-02
U 233	0.134260E+01	0.134239E+01	0.563315E+01
U 234	0.134260E+01	0.134239E+01	0.563315E+01
U 238	0.134260E+01	0.134239E+01	0.563315E+01
Np 237	0.115927E+01	0.115795E+01	0.428599E+01
Pu 238	0.836422E+00	0.833868E+00	0.122183E+01
Pu 239	0.836422E+00	0.833868E+00	0.122183E+01
Pu 240	0.836422E+00	0.833868E+00	0.122183E+01
Pu 241	0.836422E+00	0.833868E+00	0.122183E+01
Pu 242	0.836422E+00	0.833868E+00	0.122183E+01
Pu 244	0.836422E+00	0.833868E+00	0.122183E+01
Am 241	0.110881E+01	0.110754E+01	0.358202E+00
Am 243	0.110881E+01	0.110754E+01	0.358202E+00
Cm 244	0.989706E+00	0.986804E+00	0.940592E-01
Cm 245	0.989706E+00	0.986804E+00	0.940592E-01

Table 4. Comparison of WAPPAG and Directly Calculated Sensitivities to the Outside Radius of the Wasteform

Rerun perturbation	0.998985E-02
Parameter value, m	0.267300E+00
Parameter name	SRTEMP(1)

NUCLIDE	SENSITIVITY (WAPPAG)	SENSITIVITY (RERUN)	MASS OUT AFTER 10,000 YEARS
C 14	-0.193548E+01	-0.192568E+01	0.213209E+03
Se 79	0.197116E+01	0.214798E+01	0.111276E+01
Sr 90	0.247692E+01	0.250775E+01	0.517873E+02
Tc 99	0.236960E+01	0.252596E+01	0.404388E+01
Sn 126	0.240556E+01	0.255010E+01	0.423839E+00
I 129	-0.214671E+01	-0.214173W+01	0.302813E+03
Cs 135	-0.247961E+01	-0.246728E+01	0.276751E+04
Cs 137	-0.247961E+01	-0.246728E+01	0.276751E+04
Ra 226	0.111017E+01	0.151566E+01	0.727716E-05
Th 230	0.234794E+00	0.272117E+00	0.818810E-02
U 233	0.268899E+01	0.273269E+01	0.563315E+01
U 234	0.268899E+01	0.273269E+01	0.563315E+01
U 238	0.268899E+01	0.273269E+01	0.563315E+01
Np 237	0.241280E+01	0.255367E+01	0.428599E+01
Pu 238	0.195461E+01	0.215058E+01	0.122183E+01
Pu 239	0.195461E+01	0.215058E+01	0.122183E+01
Pu 240	0.195461E+01	0.215058E+01	0.122183E+01
Pu 241	0.195461E+01	0.215058E+01	0.122183E+01
Pu 242	0.195461E+01	0.215058E+01	0.122183E+01
Pu 244	0.195461E+01	0.215058E+01	0.122183E+01
Am 241	0.233614E+01	0.250435E+01	0.358202E+00
Am 243	0.233614E+01	0.250435E+01	0.358202E+00
Cm 244	0.243261E+01	0.245171E+01	0.940592E-01
Cm 245	0.243261E+01	0.245171E+01	0.940592E-01

Table 5. Comparison of WAPPAG and Directly Calculated Sensitivities to the Outer Radius of the Outermost Gap

Rerun perturbation, %	0.338989E+00
Parameter value, m	0.295000E+00
Parameter name	SRTEMP(4)

NUCLIDE	SENSITIVITY (WAPPAG)	SENSITIVITY (RERUN)	MASS OUT AFTER 10,000 YEARS
C 14	0.165940E+01	0.165378E+01	0.213209E+03
Se 79	-0.197326E+01	-0.196764E+01	0.111276E+01
Sr 90	-0.171478E+01	-0.171188E+01	0.517873E+02
Tc 99	-0.186445E+01	-0.185777E+01	0.404388E+01
Sn 126	-0.185474E+01	-0.184792E+01	0.423839E+00
I 129	0.176379E+01	0.175958E+01	0.302813E+03
Cs 135	0.198282E+01	0.197950E+01	0.276751E+04
Cs 137	0.198282E+01	0.197950E+01	0.276751E+04
Ra 226	-0.162479E+01	-0.162254E+01	0.727716E-05
Th 230	0.285323E+00	0.273961E+00	0.818810E-02
U 233	-0.177831E+01	-0.177088E+01	0.563315E+01
U 234	-0.177831E+01	-0.177088E+01	0.563315E+01
U 238	-0.177831E+01	-0.177088E+01	0.563315E+01
Np 237	-0.185288E+01	-0.184614E+01	0.428599E+01
Pu 238	-0.197794E+01	-0.197265E+01	0.122183E+01
Pu 239	-0.197794E+01	-0.197265E+01	0.122183E+01
Pu 240	-0.197794E+01	-0.197265E+01	0.122183E+01
Pu 241	-0.197794E+01	-0.197265E+01	0.122183E+01
Pu 242	-0.197794E+01	-0.197265E+01	0.122183E+01
Pu 244	-0.197794E+01	-0.197265E+01	0.122183E+01
Am 241	-0.187275E+01	-0.186621E+01	0.358202E+00
Am 243	-0.187275E+01	-0.186621E+01	0.358202E+00
Cm 244	-0.178447E+01	-0.178047E+01	0.940592E-01
Cm 245	-0.178447E+01	-0.178047E+01	0.940592E-01

Table 6. Comparison of WAPPAG and Directly Calculated Sensitivities to U-233 Mass at 5,000 Years

Rerun perturbation, %	-0.100000E+01
Parameter value, g/MTIHM	0.480000E+03
Parameter name	RADTOX(11,13)

NUCLIDE	SENSITIVITY (WAPPAG)	SENSITIVITY (RERUN)	MASS OUT AFTER 10,000 YEARS
C 14	0.000000E+00	0.000000E+00	0.213209E+03
Se 79	0.000000E+00	0.000000E+00	0.111276E+01
Sr 90	0.000000E+00	0.000000E+00	0.517873E+02
Tc 99	0.000000E+00	0.000000E+00	0.404388E+01
Sn 126	0.000000E+00	0.000000E+00	0.423839E+00
I 129	0.000000E+00	0.000000E+00	0.302813E+03
Cs 135	0.000000E+00	0.000000E+00	0.276751E+04
Cs 137	0.000000E+00	0.000000E+00	0.276751E+04
Ra 226	0.000000E+00	0.000000E+00	0.727716E-05
Th 230	0.000000E+00	0.000000E+00	0.818810E-02
U 233	0.000000E+00	0.000000E+00	0.563315E+01
U 234	0.000000E+00	0.000000E+00	0.563315E+01
U 238	0.000000E+00	0.000000E+00	0.563315E+01
Np 237	0.000000E+00	0.000000E+00	0.428599E+01
Pu 238	0.000000E+00	0.000000E+00	0.122183E+01
Pu 239	0.000000E+00	0.000000E+00	0.122183E+01
Pu 240	0.000000E+00	0.000000E+00	0.122183E+01
Pu 241	0.000000E+00	0.000000E+00	0.122183E+01
Pu 242	0.000000E+00	0.000000E+00	0.122183E+01
Pu 244	0.000000E+00	0.000000E+00	0.122183E+01
Am 241	0.000000E+00	0.000000E+00	0.358202E+00
Am 243	0.000000E+00	0.000000E+00	0.358202E+00
Cm 244	0.000000E+00	0.000000E+00	0.940592E-01
Cm 245	0.000000E+00	0.000000E+00	0.940592E-01

Table 7. Comparison of WAPPAG and Directly Calculated Sensitivities to the Gamma Ray Source at Burial

Rerun perturbation, %	-0.990000E+02
Parameter value, p/s/MTIHM	0.743600E+16
Parameter name	RGAMA(1)

NUCLIDE	SENSITIVITY (WAPPAG)	SENSITIVITY (RERUN)	MASS OUT AFTER 10,000 YEARS
C 14	0.000000E+00	0.000000E+00	0.213209E+03
Se 79	0.000000E+00	0.000000E+00	0.111276E+01
Sr 90	0.000000E+00	0.000000E+00	0.517873E+02
Tc 99	0.000000E+00	0.000000E+00	0.404388E+01
Sn 126	0.000000E+00	0.000000E+00	0.423839E+00
I 129	0.000000E+00	0.000000E+00	0.302813E+03
Cs 135	0.000000E+00	0.000000E+00	0.276751E+04
Cs 137	0.000000E+00	0.000000E+00	0.276751E+04
Ra 226	0.000000E+00	0.000000E+00	0.727716E-05
Th 230	0.000000E+00	0.000000E+00	0.818810E-02
U 233	0.000000E+00	0.000000E+00	0.563315E+01
U 234	0.000000E+00	0.000000E+00	0.563315E+01
U 238	0.000000E+00	0.000000E+00	0.563315E+01
Np 237	0.000000E+00	0.000000E+00	0.428599E+01
Pu 238	0.000000E+00	0.000000E+00	0.122183E+01
Pu 239	0.000000E+00	0.000000E+00	0.122183E+01
Pu 240	0.000000E+00	0.000000E+00	0.122183E+01
Pu 241	0.000000E+00	0.000000E+00	0.122183E+01
Pu 242	0.000000E+00	0.000000E+00	0.122183E+01
Pu 244	0.000000E+00	0.000000E+00	0.122183E+01
Am 241	0.000000E+00	0.000000E+00	0.358202E+00
Am 243	0.000000E+00	0.000000E+00	0.358202E+00
Cm 244	0.000000E+00	0.000000E+00	0.940592E-01
Cm 245	0.000000E+00	0.000000E+00	0.940592E-01

REFERENCES

1. "WAPPA: A Waste Package Performance Assessment Code," Office of Nuclear Waste Isolation (ONWI) Report ONWI-452, April 1983.

2. Harada, M. et al., "Migration of Radionuclides Through Sorbin Media, Analytical Solutions-II," Lawrence Berkeley Laboratory Report LBL-11616, ONWI-360, October 1980.

3. Wurm, K. J., S. G. Bloom and W. G. Atterbury, "TEMP: A Finite-Line Heat Transfer Code for Geologic Repositories for Nuclear Waste," Battelle Columbus Laboratories Report E517-02000, March 1985.

4. Symposium on Uncertainties Associated with the Regulation of the Geological Disposal of High-Level Radioactive Waste, Gatlinburg, Tennessee, March 9-13, 1981.

5. "Sensitivity and Uncertainty Analysis of Reactor Performance Parameters," Advances in Nuclear Science and Technology, Vol. 14, eds. J. Lewins and M. Becker, Plenum Press, New York, 1982.

6. Oblow, E. M., "An Automated Procedure for Sensitivity Analysis Using Computer Calculus," ORNL/TM-8776, Oak Ridge National Laboratory (1983).

7. Oblow, E. M., "GRESS, GRadient Enhanced Software System: Version D, User's Guide," ORNL/TM-9658, Oak Ridge National Laboratory (1985).

8. Oblow, E. M., F. G. Pin and R. Q. Wright, "Sensitivity Analysis Using Computer Calculus: A Nuclear Waste Isolation Application," Nucl. Sci. Eng. 94, 46-65 (1986).

9. Pin, F. G., B. A. Worley, E. M. Oblow and R. Q. Wright, "An Automated Sensitivity Analysis Procedure for the Performance Assessment of Nuclear Waste Isolation Systems," Nucl. and Chem. Waste Management Vol. 6 (1986).

10. Worley, B. A., R. Q. Wright, F. G. Pin and W. V. Harper, "Application of an Automated Procedure for Adding a Comprehensive Sensitivity Calculation Capability to the ORIGEN2 Point Depletion and Radioactive Decay Code," Nucl. Sci. and Eng. 94, 180-191 (1986).

11. Worley, B. A., R. Q. Wright and F. G. Pin, "Finite-Line Heat Transfer Code with Automated Sensitivity-Calculation Capability," ORNL/TM-9975, Oak Ridge National Laboratory, September 1986.

12. Pin, F. G. "Methodology for Coupling GRESS-Enhanced Versions of Computer Codes for Automated Sensitivity Analysis," ORNL/TM-10120, Oak Ridge National Laboratory (1986, in press).

ORNL/TM-9976
Dist. Category: UC-70 (Waste)

INTERNAL DISTRIBUTION

1. R. G. Alsmiller, Jr.
2. J. Barhen
3. D. G. Cacuci
4. A. G. Croff
5. J. R. Einstein
6. G. F. Flanagan
7. W. E. Ford, III
8-12. J. E. Horwedel
13. M. Goldstein
14. J. L. Lucius
15. R. E. Maerker
16. F. C. Maienschein
17. L. J. Mezga
18. F. R. Mynatt
19. E. M. Oblow
20. F. G. Pin
21. D. B. Reister
22. T. H. Row
23. L. D. Trowbridge
24-28. C. R. Weisbin
29-33. B. A. Worley
34. R. Q. Wright
35. A. Zucker
36. P. W. Dickson, Jr. (Consultant)
37. G. H. Golub (Consultant)
38. R. M. Haralick (Consultant)
39. D. Steiner (Consultant)
40. RSIC
41-42. Central Research Library
43. Division Advisory Committee
44. Laboratory Records, RC
45. ORNL Y-12 Technical Sec.
46. ORNL Patent Office
47-51. EP&MD Reports Office

EXTERNAL DISTRIBUTION

52. Office of Assistant Manager for Energy Research and Development, DOE-ORO, Oak Ridge, TN 37830

53. Sandy Perkins, Research and Waste Management Division, U.S. DOE-ORO, Oak Ridge, TN 37830

54. G. Appel, Salt Repository Project Office, 505 King Avenue, Columbus, OH 43201

Rockwell Hanford Co., P.O. Box 800, Richland, WA 99352

55. L. C. Brown
56. P. M. Clifton
57. C. DeFigh-Price
58. C. J. Geier
59. C. McLane
60. B. Sager
61. J. Sonnicksen
62. R. Wild
63. D. Wood

Battelle Memorial Institute, Office of Nuclear Waste Isolation, 505 King Avenue, Columbus, OH 43201

64. W. A. Carbiener
65. N. E. Carter
66. S. K. Gupta
67. W. V. Harper
68. W. M. Hewitt
69. G. Jansen
70. J. F. Kircher
71. E. Meadow
72. P. Moehler
73. J. Parry
74. G. E. Raines
75. R. E. Thomas
76. ONWI Library

Pacific Northwest Laboratory, P.O. Box 999, Richland, WA 99352

77. M. Apted
78. C. Cole
79. P. Doctor
80. R. Erikson
81. M. Foley
82. A. Liebetrau
83. M. Piepho
84. S. Sneider

Sandia National Laboratories, P.O. Box 5800, Albuquerque, NM 87185

85. R. Cranwell
86. R. L. Iman

U.S. DOE-BWIPO, Richland, WA 99352

87. D. H. Dahlem
88. P. E. Lamont
89. M. K. Thompson

90. Donald Alexander, U.S. DOE, Civilian Radioactive Waste Management Program, 1000 Independent Ave., SW, Washington, D.C. 20585

91. C. Koplik, The Analytic Sciences Corporation, 1 Jacob Way, Reading, MA 10867

92. W. J. Kurzeka, Manager, Commercial Waste Tech. Unit, Rockwell Hanford Operations, P.O. Box 800, Richland, WA 99352

93. D. Langmuir, Department of Chemistry and Geochemistry, Colorado School of Mines, Golden, CO 80401

94. W. L. Lee, R. F. Weston, Inc., 2301 Research Blvd., Rockville, MD 20850

95. J. A. Lieberman, OTHA, Inc., P.O. Box 651, Glen Echo, MD 20812

96. J. O. Neff, U.S. Department of Energy, Richland Operations Office, 505 King Avenue, Columbus, OH 43201

97. T. H. Pigford, Department of Nuclear Engineering, University of California, Berkeley, CA 94720

98. J. Rhoderick, U.S. DOE/OCRWM, 1000 Independence Ave., SW, Washington, D.C. 20585

99-407. For distribution as shown in TID-4500, Distribution category UC-70 - Nuclear Waste Management