

**VACUUM PUMPING SYSTEM
FOR A LARGE IFE TARGET CHAMBER***

¹C.A. Gentile, ¹R.F. Parsells, ¹C. Priniski, ¹S.Langish, ¹W. Blanchard,
¹F. Dahlgren and ²J. Sethian

¹ Princeton Plasma Physics Laboratory, P.O. Box 451, Princeton, New Jersey 08543

² Naval Research Laboratory, 4551 Overlook Avenue, Washington D.C 20375

cgentile@pppl.gov

In support of The High Average Power Laser (HAPL) Program, the Princeton Plasma Physics Laboratory has designed a vacuum pumping system (VPS) for an Inertial Fusion Energy (IFE) target chamber. The VPS is designed to maintain a base operating pressure of ≤ 1 m torr during a cyclic gas load (for full operation at 5 Hz) of 141 torr-liters/sec. The 1.15 M liter target chamber is fitted with a mid-plane 145 K liter torodial duct, which incorporates 60 pumping vents, providing the physical platform for the resident 120 Turbo Molecular Pumps (TMP) (2 TMPs/vent). The TMPs are configured to continuously pump on the target chamber during pulsed operations. System in-leakage is assumed to be 1×10^{-5} torr which is consistent with vacuum chambers of similar size and complexity. The (6,000 l/sec) TMPs, which are located in a 1 kG field along the torodial duct, are magnetically shielded to an attenuated field of 50 gauss. Sixty beam ports interface with the target chamber providing a clear line of sight for the converging laser light to implode the target(s). The vacuum pumping system employs, to the largest extent possible, commercial off the shelf components (COTS) with a proven record of high operational availability in similar magnetic fusion energy (MFE) applications. The system has been designed to transition from D-D to D-T operation with minimal configuration change. The system has been estimated to cost ~\$15 M. This paper will discuss the full design in detail.

*Work supported by U.S. DOE Contract No DE-AC02-76CH03073.