

**OVERVIEW OF THE US ITER DUAL COOLANT LIQUID BREEDER (DCLL)
TEST BLANKET MODULE PROGRAM**

C.P.C. Wong, M. Abdou,¹ S. Malang,² M. Sawan,³ M. Dagher,¹
S. Smolentsev,¹ B. Merrill,⁴ M. Youssef,¹ S. Sharafat,¹ P. Calderoni,
G. Sviatoslavsky,³ D.K. Sze,⁵ N. B. Morley,¹ R. Kurtz,⁶ S. Willms,⁷

D.P. Carosella, M.P. Labar, P. Fogarty,⁸ S. Zinkle⁸

General Atomics, P.O. Box 85608, MS 13-254, San Diego, CA 92186-5608

¹University of California, Los Angeles, California

²Fusion Nuclear Technology Consulting, Linkenheim, Germany

³University of Wisconsin, Madison, Wisconsin

⁴INEEL, Idaho Falls, Idaho

⁵University of California, San Diego, California

⁶LANL, Los Alamos, New Mexico

⁷Pacific Northwest Laboratory, Richland, Washington

⁸Oak Ridge National Laboratory, Oak Ridge, Tennessee

wongc@fusion.gat.com

With the US rejoining ITER, the US chamber technology community has participated in discussion in the ITER Test Blanket Working Group (TBWG) and has proposed to develop, in collaboration with other parties, solid and liquid breeder blanket concepts to be tested in ITER. Presently, the focus on the liquid breeder option is the dual coolant helium-cooled reduced activation ferritic steel structure with self-cooled Pb-17Li breeder (DCLL) that uses flow coolant insert (FCI) as the MHD and thermal insulator. When projected for a reference tokamak power reactor design, it has the potential for a gross thermal efficiency of > 40%. The US is planning for an independent test blanket module (TBM) that will occupy half an ITER test port with corresponding supporting ancillary equipment. An initial design, testing strategy and corresponding test plan have been completed for the DCLL concept. The DCLL TBM design for the integrated testing phase, including the choice of configuration, relevant design analyses, ancillary equipment, testing strategy and corresponding test plan will be presented in this paper.