

---

**Oak Ridge National Laboratory (ORNL)  
Transportation and Packaging Management (TPM)  
Container Preparation and Filling Instructions/Checklist**

**Type A 7A Drums – 30 Gallon Size**

**ORNL-PKG-04, Rev. 0**

Issued: 2/27/1997

Revised: N/A

Page 1 of 2

---

**INSTRUCTIONS:** Complete the activities requested below following the instructions in Section A.

**NOTE 1:** Type A 7A Drums are used for ***solid material only***.

**NOTE 2:** The maximum gross weight is 400 pounds for Type A use. [ORNL drum UN marked 160 kg (350 lb) minimum].

**NOTE 3:** The 30 gallon open head drum has the correct gauge, bolt closure, and gasket to meet Type A requirements. The drum matches specifications in the "Test and Evaluation Documentation for DOT Specification 7A, Type A Packaging," DOE/RL-96-57, Westinghouse Hanford Company test report book. The DOE/RL-96-57 has test documentation and user requirements for DOT Specification drums (17C) which are no longer manufactured. Since ORNL TPM has procured UN1A2 drums the specifications of the tested drum(s), the DOE/RL-96-57 documentation also applies to this drum.

**NOTE 4:** The DOE/RL-96-57 test report book defines three forms of solid materials. The shipper must determine the most appropriate form for the contents to be shipped. The three forms are as follows:

- " Form No. 1 - Solids: any particle size.
- " Form No. 2 - Solids: large particle size only (e.g., sand, concrete, debris, soil).
- " Form No. 3 - Solids: objects with no significant dispersible or removable contamination (see 49 CFR ¶173.443).

**A. UN1A2 (30 Gallon Size)  
Stores Catalog No. 02-112-6330  
Stores Catalog No. 02-112-6050 (*available at Y-12 only*)**

**Operating  
Personnel**

1. Visually inspect the drum, lid, and locking ring for rust, damage, dents, and defects.
2. Visually inspect the lid gasket for wearing or tears.
3. Report any deficiencies to the Packaging Supervisor.
4. Securely position the contents.
5. **IF** the contents are "Form No. 1," **THEN**  
Apply the RTV Sealant (or equivalent) to the surface of the gasket in contact with the drum body.
6. Close the drum with a 5/8" bolt with jam nut (supplied with drum).

**FOR INTERNAL USE ONLY**

---

## Container Preparation and Filling Instructions/Checklist

Type A 7A Drums – 30 Gallon Size

ORNL-PKG-04, Rev. 0

Issued: 2/27/1997

Revised: N/A

Page 2 of 2

---

### A. UN 1A2 (30 Gallon Size)

Stores Catalog No. 02-112-6330

Stores Catalog No. 02-112-6050 (*available at Y-12 only*)

#### Operating Personnel

7. Tap around the closing ring with a hammer and tighten the bolt to 40 (+/- 4) ft-lb torque.

The jam nut should be tightened to prevent unintentional loosening during transit.

8. Mark the drum to indicate "Radioactive Material, USA DOT 7A TYPE A."
9. Attach a plain wire seal for nonaccountable materials or a controlled, numbered seal for accountable materials, if required.

Seal wires should be threaded through the lugs in the closing ring or through holes provided in the bolt and/or lugs as appropriate for each container. The seal must be installed so that it has to be broken to open a container.

10. Record the controlled, numbered seal information on the Seal Log Sheet, if applicable.

Prepared by: ORNL TPM Organization

Approved by: Jeff Shelton

May 25, 2001

Jeff Shelton, Manager (576-6401)  
ORNL TPM - Packaging Operations

**FOR INTERNAL USE ONLY**