

**Redox Potential of Novel Electrochemical Buffers
Useful for Corrosion Prevention in Molten Fluorides**

G. D. Del Cul, D. F. Williams, L. M. Toth
Oak Ridge National Laboratory
Oak Ridge TN 37831-6224

Advanced High-Temperature Reactors (AHTRs) that have improved safety features and more efficient energy conversion systems constitute a new generation of nuclear power reactors. A molten-fluoride cooled version of the High Temperature Gas-cooled Reactor (HTGR) offers the benefits of high thermodynamic efficiency, additional fission product containment, and several enhanced safety features (low-pressure operations, passive cooling).

The primary technical hurdle for use of molten salts at higher temperatures (~1000°C) is materials performance. Understanding the role of corrosion and preventing materials degradation is the key requirement. During the Molten Salt Reactor Program it was established that a controlled, mildly reducing environment improves the compatibility of the container with a molten salt. For molten salt fuels this was established using the U(IV/III) soluble redox couple as an electrochemical buffer. For actinide-free molten salt coolants operating at very high temperatures in an AHTR, we propose a new set of redox buffers: Tm(III/II), Sm(III/II), Yb(III/II), V(III/II) and Eu(III/II). Work in related chloride and fluoride salts (Table 1) suggests that these redox-sensitive rare earths (and vanadium) are the most useful candidates for preventing container corrosion. Our present interest is in "FLiNaK" LiF-NaF-KF (46.5-11.5-42 mol %) and LiF-MgF₂ (66-34 mol %) as prototypical coolant salts. The experimentally determined standard redox potentials of these new electrochemical buffers are compared with the literature on analogous chloride systems, and related fluoride systems.

- [1] Baes, C. F., "The Chemistry and Thermodynamics of Molten Salt Reactor Fuels," in *Nuclear Metallurgy* 15, P. Chiotti ed., p. 617-644 (1970).
- [2] Johnson, K. E., and MacKenzie, J. R., "Samarium, Europium, and Ytterbium Electrode Potentials in LiCl-KCl Eutectic," *J. Electrochem. Soc.* **116(12)**, p. 1697-1703 (1969).
- [3] F. Caligara, L. Martinot, and G. Duyckaerts, "Contribution to the Knowledge of Electrochemistry of Uranium in LiCl-KCl Eutectic" *Bull. Soc. Chim. Belges* **76**, p. 5-14 (1967).
- [4] Palmbeck, J. A., "Electromotive Force Series in Molten Salts," *J. Chem. Eng. Data* **12**, p.77-81 (1967).
- [5] Jenkins, H. W., Mamantov, G., and D. L. Manning, "Electrode Potentials of Several Redox Couples in Molten Fluorides," *J. Electrochem. Soc.* **117(2)**, p. 183-185 (1970).

Redox couples	Standard reduction potential (V)	
	LiCl-KCl at 450°C	2LiF-BeF ₂ at 700°C
Li(I) – Li(0)	-3.62	-2.56
Mg(II) – Mg(0)	-2.88	–
Be(II) – Be(0)	–	-1.765
Zr(IV) – Zr(0)	-2.13	-1.355
Sm(III) – Sm(II)	-2.035	–
Yb(III) – Yb(II)	-1.68	–
U(IV) – U(III)	-1.55	-1.045
V(III) – V(II)	-1.07	–
Eu(III) – Eu(II)	-0.86	–
Reference couples		
HF – ½ H ₂	–	0
½ Cl ₂ – Cl ⁻	0	–

Table 1. Electrochemical measurement of redox couples in chlorides and fluorides (from references [1-5]).

