

**Results of the Independent
Radiological Verification
Survey at 5 Hancock Street,
Lodi, New Jersey
(LJ029V)**

**R. E. Rodriguez
C. A. Johnson**

DRAFT

LIFE SCIENCES DIVISION

Department of the Army - Corps of Engineers
(Activity No. 43WM11202; DAG)

**Results of the Independent Radiological Verification
Survey at 5 Hancock Street, Lodi, New Jersey (LJ029V)**

R. E. Rodriguez and C. A. Johnson

Draft Issued - May 1999

Investigation Team

R. D. Foley—Measurement Applications and Development Manager
M. E. Murray—FUSRAP Project Director
R. E. Rodriguez—Survey Team Leader

Survey Team Members

R. E. Rodriguez R. D. Foley

DRAFT

Work performed by the
Measurement Applications and Development Group

Prepared by the
OAK RIDGE NATIONAL LABORATORY
Oak Ridge, Tennessee 37831-6285
managed by
LOCKHEED MARTIN ENERGY RESEARCH CORP.
for the
U. S. DEPARTMENT OF ENERGY
under contract DE-AC05-96OR22464

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615) 576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency, thereof, nor any of their employees, makes any warranty, express, or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

CONTENTS

LIST OF FIGURES	v
LIST OF TABLES	v
ACKNOWLEDGMENTS	vii
ABSTRACT	ix
INTRODUCTION	1
SCOPE OF THE SURVEY	2
VERIFICATION SURVEY AND ANALYSIS	3
CONCLUSIONS	4
REFERENCES	5

LIST OF FIGURES

1	Diagram showing general location of the Stepan property and the Maywood Interim Storage Site in relation to Hancock Street, Lodi, New Jersey	6
2	Diagram of the property at 5 Hancock Street, Lodi, New Jersey, showing gamma measurements and locations of soil samples	7

LIST OF TABLES

1	Applicable guidelines for protection against radiation	8
2	Background radiation levels and concentrations of selected radionuclides in soil samples in the northern New Jersey area	9
3	Concentrations of selected radionuclides in soil samples collected at 5 Hancock Street, Lodi, New Jersey (LJ029V)	10

ACKNOWLEDGMENTS

This project was sponsored by the U.S. Army Corps of Engineers, New York District, under contract number 43WM11202 with Lockheed Martin Energy Research Corp. The authors wish to acknowledge the contributions of the surveying staff, D. A. Roberts, and D. A. Rose of the Measurement Applications and Development Group, Life Sciences Division, Oak Ridge National Laboratory, for their participation in collecting, reporting, and analyzing the data for this effort. A special thanks to M. S. Uziel for assisting with the graphics.

ABSTRACT

This report documents the results of an independent radiological verification survey of the property at 5 Hancock Street, Lodi, New Jersey. The survey was conducted in April 1998 by a team from the Life Sciences Division of the Oak Ridge National Laboratory (ORNL). Independent verification of completed cleanup work at Formerly Utilized Sites Remedial Action Program (FUSRAP) sites is performed and documented according to prescribed procedures prior to certification of the property for release for unrestricted use. Prior to remediation, thorium residues in excess of applicable guidelines were found in portions of the yard on this property.

A thorough investigation of the outdoor property at 5 Hancock Street was conducted after remediation to confirm that all radioactive residues above applicable guidelines had been removed by the project management contractor. The survey included directly measured radiation levels and soil sample collection and analysis to determine concentrations of thorium and certain other radionuclides, and to compare these data to the guidelines.

The results of the independent verification survey of the property demonstrate that all contaminated areas have been remediated to radionuclide concentrations and activity levels below the applicable current guideline limits.

Based on a review of the project management contractor's radiological survey data and confirmed by the verification survey data, all radiological measurements fall below limits prescribed by radiological guidelines established for this site, and it is concluded that the remediation activities at 5 Hancock Street, Lodi, New Jersey, satisfy the objectives of the FUSRAP program.*

*The Post Remedial Action Report for this property, which will be issued by the remedial action contractor, has not been received or reviewed by ORNL. When this document is received and reviewed, and USACE comments are incorporated, a final report will be issued.

**Results of the Independent Radiological
Verification Survey at
5 Hancock Street, Lodi, New Jersey
(LJ029V)***

INTRODUCTION

Processing of thorium ores was performed in Maywood New Jersey between 1916 and 1959 by the Maywood Chemical Works (MCW)¹, partially under contract to the Atomic Energy Commission (AEC). In 1959, the MCW ceased thorium processing and the 30-acre property was sold to Stepan Chemical Company. During the early years of operation, MCW stored the wastes and residues in low-lying areas west of the processing facilities, in what is now called the Maywood Interim Storage Site (MISS). The waste produced by the thorium extraction process was a sand-like material containing residual amounts of thorium and its decay products, with smaller quantities of uranium and its decay products.

Residuals containing radioactive materials subsequently migrated off-site to the surrounding area, and the Stepan property and several vicinity properties were designated by Congress for remedial action as a result of the 1984 Energy and Water Development Appropriations Act, and later were included as a decontamination research and development project under the Department of Energy's (DOE) Formerly Utilized Sites Remedial Action Program (FUSRAP).

Some area residents had used the sand-like wastes as mulch in their yards. Additionally, some of the contaminated wastes were apparently eroded from the site and carried downstream by Lodi Brook, a small stream flowing south from Maywood with its headwaters near the Stepan waste storage site. From the 1940s to the 1970s, the stream was diverted underground and its course altered several times, resulting in the movement of contaminated soil to the surface where, in some cases, it was covered over or mixed with clean fill. Thus, even in the absence of surface contamination, some properties in question were drilled in search of former stream bed material. At the request of the DOE, Oak Ridge National Laboratory (ORNL) conducted investigative radiological surveys of this and other properties surrounding the former processing plant.

In October 1985, a radiological survey of the ground surface was conducted on this private, residential property by the Measurement Applications and Development (MAD) Group at ORNL.² In September 1986, a follow up subsurface investigation was performed. Results of the surveys indicated that the property contained ²³²Th concentra-

*The survey was performed by members of the Measurement Applications and Development Group of the Life Sciences Division of Oak Ridge National Laboratory under DOE contract DE-AC05-96OR22464.

tions in excess of the relevant criteria.

In the spring of 1998, the project management contractor for FUSRAP, Bechtel National, Incorporated (BNI), directed the decontamination of the 5 Hancock Street property to current guidelines. The location of Hancock Street and Lodi, New Jersey, relative to the Stepan property and the Maywood Interim Storage Site is shown in Fig. 1.

The radiological verification survey was conducted in April 1998, shortly after remediation efforts of the property, by a team from ORNL's MAD Group. Verification surveys are performed in response to the Environmental Restoration Program requirements. These requirements dictate that independent verification of completed cleanup work at FUSRAP sites shall be performed and documented according to prescribed procedures prior to certification of the property for release for unrestricted use.^{3,4}

This report documents the results of an independent radiological verification survey of the private, residential property at 5 Hancock Street. The verification survey was conducted to confirm that radioactive residuals previously identified in the back yard had been remediated to bring the property into compliance with current guidelines. Radiological guidelines are currently those provided by DOE for these FUSRAP properties.

The property at 5 Hancock Street is a two-story, wood frame house with an attached wood deck in the back yard and concrete walkways in the front. At one time an above-ground pool was located in the back yard near the property line, and an asphalt driveway was located in the excavated area along the side of the house. (Fig. 2).

SCOPE OF THE SURVEY

Objectives

The objectives of the verification activities were to confirm (1) that available documentation adequately and accurately describes the post-remedial condition of the property that is to be verified, and (2) that the remedial action reduced contamination levels to within authorized limits. Applicable DOE guidelines for protection against radiation are shown in Table 1.

Survey Methods

A comprehensive description of the survey methods and instrumentation used in this survey is given in *Procedures Manual for the ORNL Radiological Survey Activities (RASA) Program*, ORNL/TM-8600 (April 1987)⁵ and *Measurement Applications and Development Group Guidelines*, ORNL-6782 (January 1995).⁶

The radiological verification survey of this property included (1) a complete surface gamma scan of the property outdoors, (2) the collection of soil samples for analysis, and (3) the examination of additional data collected by BNI and its radiological support subcontractor, Scientific Ecology Group, Inc. (SEG). Gamma radiation levels were determined using a portable sodium iodide (NaI) gamma scintillation probe connected to a Victoreen Model 490 Thyac III ratemeter. Measurements were recorded in counts per minute (cpm) and converted to microrentgen per hour ($\mu\text{R/h}$.)

One large area at the north end of the backyard of 5 Hancock Street was excavated and remediated by BNI. Surface (0 to 15 cm) soil samples were collected at various locations over the property, mainly in the excavated area in the backyard. Excavations were up to 3.5 ft deep. Systematic soil samples (VS1 through VS3) were taken from the excavated area irrespective of gamma exposure rates. Two biased samples (VB1 and VB2) were collected at the points of the highest surface gamma. All soil samples were collected after excavation was completed and before a remediated area was backfilled with clean soil. Concentrations of ^{226}Ra , ^{232}Th , and ^{238}U were determined in soil samples using gamma spectrometry.

VERIFICATION SURVEY AND ANALYSIS

Table 1 summarizes current guidelines for sites included within FUSRAP and Table 2 lists typical background radiation levels for the Lodi, New Jersey area. These data are provided for purposes of comparison with the survey results presented in this section. All measurements presented in this report are gross (total) readings; background radiation levels have not been subtracted. Similarly, background concentrations have not been subtracted from radionuclide concentrations in soil samples.

Gamma Exposure Rates

Gamma measurements were recorded in counts per minute (cpm) and converted to microrentgen per hour ($\mu\text{R/h}$). Surface gamma exposure rates generally ranged from 8 to 13 $\mu\text{R/h}$ in the front yard, and from 10 to 20 $\mu\text{R/h}$ in the excavated area in the back yard (see Fig. 2). A maximum of 25 $\mu\text{R/h}$ was measured in a small area ($\sim 4 \text{ m}^2$) in the far northeast corner of the back yard near the property line. These measurements are comparable to or slightly higher than the natural background levels for this area of New Jersey (Table 2), and biased as well as systematic soil samples were taken from these areas to analyze for radionuclide concentrations.

Soil Samples

Five soil samples were collected from the back yard, including two biased samples taken in or near the excavated area at the north end of the property. Systematic samples are collected without regard to measured gamma radiation levels. Biased samples are collected at locations of very slightly elevated surface gamma exposure rates. The samples were analyzed for radium (^{226}Ra), thorium (^{232}Th), and uranium (^{238}U). Soil sample locations are shown on Fig. 2, and results of radionuclide analyses are listed in Table 3.

Radionuclide concentrations of ^{226}Ra in both systematic and biased samples ranged from 0.98 to 2.1 pCi/g. Concentrations of ^{232}Th in systematic and biased samples ranged from 1.6 to 2.6 pCi/g. These values are slightly above background concentrations for the area, but well below the current guidelines for these radionuclides in soil. The guideline for ^{226}Ra and ^{232}Th is 5 pCi/g above background averaged over 100 m² for surface and subsurface soil for this site (see Table 1).

Concentrations of ^{238}U in soil ranged from 1.5 to 2.4 pCi/g in both systematic and biased samples. These values are well below the site specific guidelines of 100 pCi/g for total uranium (50 pCi/g for ^{238}U averaged over 100 m² for uranium in soil (Table 1). Soil analyses are shown in Table 3.

CONCLUSIONS

Prior to remediation, thorium residues in excess of applicable guidelines were found in the back yard on the north end of the property at 5 Hancock Street, Lodi, New Jersey. Decontamination, which consisted of excavation and removal of contaminated soil and backfilling with clean soil, was performed by subcontractors under the direction of BNI.

The remediated areas on the grounds of the property were thoroughly investigated for radionuclide residues. Surface gamma exposure rates were below guideline levels and comparable to typical background values for the area. The results of soil radionuclide analysis for ^{238}U , ^{226}Ra , and ^{232}Th indicated that all soil concentration measurements were below limits prescribed by the DOE applicable guidelines for protection against radiation.

Results of the independent radiological verification survey of this property by ORNL confirm that the remedial action has reduced contamination levels to within authorized limits.

Based on a review of the project management contractor's radiological survey data,

and confirmed by the verification survey data, all radiological measurements fall below the limits prescribed by current radiological guidelines established for this site, and the property at 5 Hancock Street, Lodi, New Jersey, successfully meets the remedial action objectives.

(Note: The Post Remedial Action Report for this property, which will be issued by the remedial action contractor, has not been received or reviewed by ORNL. When this document is received and reviewed, and USACE comments are incorporated, a final report will be issued).

REFERENCES

1. L. W. Cole, J. Berger, P. Cotten, R. Gosslee, L. Sowell, and J. Weaver, *Radiological Assessment of Ballod Associates Property (Stapan Chemical Company), Maywood, New Jersey*, Oak Ridge Associated Universities, Oak Ridge, Tenn., July 30, 1981.
2. W. D. Cottrell, L. M. Floyd, M. W. Francis, J. O. Mynatt, *Results of the Radiological Survey at 5 Hancock Street, Lodi, New Jersey (LJ029)*, ORNL/RASA-87/33, September 1989.
3. *Verification and Certification Protocol—Supplement No. 2 to the FUSRAP Summary Protocol, Rev. 1*, U.S. DOE, Division of Facility and Site Decommissioning Projects, Office of Nuclear Energy, November 1985.
4. R. P. Whitfield, Deputy Assistant Secretary for Environmental Restoration, U.S. DOE, memorandum to J. J. Fiore, Director, Office of Eastern Area Programs, Office of Environmental Restoration, U.S. DOE, May 6, 1992.
5. T. E. Myrick, B. A. Berven, W. D. Cottrell, W. A. Goldsmith, and F. F. Haywood, *Procedures Manual for the ORNL Radiological Survey Activities (RASA) Program*, ORNL/TM-8600, Martin Marietta Energy Systems, Inc., Oak Ridge Natl. Lab., April 1987.
6. Oak Ridge National Laboratory, Health Sciences Research Division, *Measurement Applications and Development Group Guidelines*, ORNL-6782, Martin Marietta Energy Systems, Inc., January 1995.



Fig. 1. Diagram showing general location of the Stepan property and the Maywood Interim Storage Site in relation to Hancock Street, Lodi, New Jersey.




Fig. 2. Diagram of the property at 5 Hancock Street, Lodi, New Jersey, showing gamma measurements and locations of soil samples.

Table 1. Applicable guidelines for protection against radiation
(Limits for uncontrolled areas)

Mode of exposure	Exposure conditions	Guideline value
Radionuclide concentrations in soil (generic)	Maximum permissible concentration of the following radionuclides in soil above background levels, averaged over a 100-m ² area ²²⁶ Ra ²³² Th	5 pCi/g averaged over the first 15 cm of soil below the surface; 15 pCi/g when averaged over 15-cm-thick soil layers more than 15 cm below the surface ^{a,b}
Derived concentrations	Total uranium	100 pCi/g ^c
Guideline for non-homogeneous contamination (used in addition to the 100-m ² guideline) ^d	Applicable to locations with an area ≥ 25 m ² , with significantly elevated concentrations of radionuclides ("hot spots")	$G_A = G_i(100/A)^{1/2}$, where G_A = guideline for "hot spot" of area (A) G_i = guideline averaged over a 100-m ² area

^aFor residential properties in the Lodi, New Jersey, area, the guideline for ²²⁶Ra and ²³²Th is 5 pCi/g above background levels, averaged over a 100-m² area, for both surface and subsurface soil. *Sources:* W. J. Muszynski, Deputy Regional Administrator, Environmental Protection Agency, Region II, correspondence to J. La Grone, Manager, Oak Ridge Operations Office, Department of Energy, March 1994; and J. La Grone, Manager, Oak Ridge Operations Office, Department of Energy, correspondence with Muszynski, Deputy Regional Administrator, Environmental Protection Agency, Region II, April 1994.

^bThe concentration of any single radionuclide above normal background levels shall not exceed the guideline value. If more than one radionuclide is present, the sum of the ratios of the measured soil concentration of each radionuclide to its corresponding guideline value shall not exceed unity.

^cDOE guidelines for uranium are derived on a site-specific basis. A guideline of 100 pCi/g for total uranium above background levels has been approved for this site. *Source:* J. W. Wagoner II, Environmental Restoration, Department of Energy, memorandum to L. Price, Oak Ridge Operations Office, Department of Energy, April 1994.

^dDOE guidelines specify that every reasonable effort shall be made to identify and to remove any source that has a concentration exceeding 30 times the guideline value, irrespective of area. *Source:* Adapted from *Revised Guidelines for Residual Radioactive Material at FUSRAP and Remote SFMP Sites*, April 1987.

Sources: Adapted from U. S. Department of Energy, *Radiation Protection of the Public and the Environment*, DOE Order 5400.5, April 1990 and U.S. Department of Energy, *Guidelines for Residual Radioactive Material at FUSRAP and Remote SFMP Sites*, Rev. 2, March 1987; and U. S. Department of Energy *Radiological Control Manual*, DOE N5480.6 (DOE/EH-256T), June 1992.

Table 2. Background radiation levels and concentrations of selected radionuclides in soil samples in the northern New Jersey, area

Type of radiation measurement or sample	Radiation level or radionuclide concentration	
	Range	Average
Gamma exposure rate at 1 m above ground surface ($\mu\text{R/h}$)	3–13 ^a	8 ^b
Concentration of radionuclides in soil (pCi/g dry wt) ^c		
²²⁶ Ra	0.55– 1.4	1.0
²³² Th	0.53– 1.5	1.0
²³⁸ U	0.46– 1.4	1.0

^aValues obtained from 14 locations in the northern New Jersey area. *Source:* T. E. Myrick, B. A. Berven, and F. F. Haywood, *State Background Radiation Levels: Results of Measurements Taken During 1975-1979*, ORNL/TM-7343, Union Carbide Corp., Oak Ridge Natl. Lab., November 1981.

^bU.S. Department of Energy, *Radiological Survey of the Middlesex Municipal Landfill, Middlesex, New Jersey*, DOE/EV-0005/20, April 1980.

^cValues obtained from 15 locations in the northern New Jersey area. *Source:* Myrick et al., ORNL/TM-7343, 1981.

DRAFT

Table 3. Concentrations of selected radionuclides in soil samples collected at 5 Hancock Street, Lodi, New Jersey (LJ029V)

Sample ID ^b	Depth (cm) ^c	Radionuclide concentration (pCi/g) ^a		
		²³² Th	²³⁸ U	²²⁶ Ra
<i>Systematic samples^d</i>				
VS1	0–15	1.7 ± 0.2	2.0 ± 0.3	2.1 ± 0.2
VS2	0–15	2.6 ± 0.3	1.6 ± 0.3	1.2 ± 0.1
VS3	0–15	1.7 ± 0.2	2.4 ± 0.4	2.1 ± 0.2
<i>Biased samples^e</i>				
VB1	0–15	1.6 ± 0.2	1.5 ± 0.3	0.98 ± 0.1
VB2	0–15	1.9 ± 0.2	2.2 ± 0.3	1.9 ± 0.1

^aIndicated counting error is at the 95% confidence levels ($\pm 2\sigma$). Background concentrations (see Table 2) have not been subtracted.

^bSample locations are shown on Fig. 2.

^cSamples were taken after completion of excavation and before a remediated area was backfilled with clean soil.

^dSystematic samples are collected without regard to measured gamma radiation levels.

^eBiased samples are collected at locations of very slightly elevated surface gamma exposure rates.